

#startupindia



Fabrication, Customisation and Supply of Defense Products, Solid Waste ManagementCIN: U90001RJ2019PTC066650deftech.greenindia@gmail.comGST: 08AAHCD4702G1ZV

PROSPIKE 1600 Series





The PROSpike 1600 series is a Portable and an On Demand Spike Deployment

SYSTEM AVAILABLE IN TWO DIFFERENT VERSIONS

Connected to Power Source PS-1625Y / PS1625B: Like PS-1620 mod el but with ability to charge and fire (unlimited) While connected to a 110 220V power source. When used as stand alone the unit will fire 8 times.

Battery Powered PS-1630 Y 1 PS1630B: (NATO model) The replaceable battery fires 24 times before it needs to be recharged. Recharge able from a standard car battery. 1630 model has the ability to pair with other units (1630 or up) thus increasing the reach of the spike strip from 5.5 to 11 meters with a single remote control. The remote control uses smart technology. The 1630 mode I has a GPS unit including time registration f or capturing data when the PROSpike is deployed.



DEFTECH & GREENINDIA PVT LTD

Aidan Bhavan, Plot-32, First Polo, Paota, Jodhpur (Raj), PIN: 342006 INFO@DGPL.ONLINE, Mob: +91 941 40 234 33/ +91 979 94 709 09



#startupindia



Fabrication, Customisation and Supply of Defense Products, Solid Waste ManagementCIN: U90001RJ2019PTC066650deftech.greenindia@gmail.comGST: 08AAHCD4702G1ZV

PROSPIKE 1600 Series

Technical Specifications

| Models | 1625 | 1630 |
|--|-----------------|-----------------|
| Remote Control | | |
| Transmission frequency 433.3 Mhz | Y | Y |
| Subject to licensing (EU) | <10Mw | 10Mw |
| Reach | 100 m | 100 m |
| LCD Display | Y | Y |
| Pressure indicator | Y | Y |
| Remaining cycles on battery | Y | Y |
| Remaining cycles untill interval service | Y | Y |
| Remaining cycles untill maintenance | Y | Y |
| Selftest remote control | Y | Y |
| SmartKey | Y | Y |
| Pairing ability | | Y |
| Fault notification code | | Y |
| Battery | | |
| Replacable battery 8 cycles | Y | |
| Replacable battery 24 cycles | | Y |
| Recharging time quick charge in minutes | 30 | 30 |
| ВоҮ | | |
| Weight in kg | 23,5 | 23,5 |
| Dimensions in mm (LYWYH) with handle and dome | 833 X 520 X 140 | 833 X 520 X 140 |
| Dimensions in mm (LYWYH) without handle and dome | 833 X 462 X 120 | 833 X 462 X 120 |
| Deployment time in seconds | <2 sec | <2 Sec |
| Retraction time in seconds | <1 sec | <1 sec |
| Set up time in seconds | <30 sec | <30 sec |
| GPS module | No | Yes |
| Logbook available for enduser | No | Yes |
| Main circuit breaker On / O switch | Yes | Yes |
| Standard replacement spikes | 10 | 10 |

For Further Details Pls Contact @ 9414023433

DEFTECH & GREENINDIA PVT LTD

Aidan Bhavan, Plot-32, First Polo, Paota, Jodhpur (Raj), PIN: 342006 INFO@DGPL.ONLINE, Mob: +91 941 40 234 33/ +91 979 94 709 09